






HIGH-BRIGHTNESS
HIGH-CONTRAST
BLACK-FACE
QUICK-LOCK-SYSTEM
MAGNETIC FAST-RIGG
CLIMBABLE FRAME
FAST REPLACEABLE BACKBOX

| | |
|---------------------------|---|
| Pixelpitch | 2,9 mm |
| Helligkeit | 1.600 Nits kalibriert (1.800 max.) |
| SMD-Typ | Nationstar 2121 3-in-1 RGB |
| SMD Merkmale | Full-Black, High-Brightness, High-Contrast, High-Level |
| Farbtiefe | 16 Bit pro Farbkanal |
| Auflösung | 168 x 168 Pixel |
| LED Treiberchip | MBI5252 |
| Receivingcard | MRV270 |
| Scantyp | 1/14 |
| Refreshrate | ≥ 3840 Hz |
| Horiz. Blickwinkel | +85°/-85° |
| Vert. Blickwinkel | +85°/-85° |
| Kontrast | > 5.000:1 |
| Nennleistung in W | Typisch 60W / max. 160W |
| Spannungsbereich | AC 88-264V/ 50-60 Hz |
| Stromanschluss | NeutrikpowerCON |
| Abmessungen | 500 x 500 x 100 mm (BxHxT) |
| Gewicht | 9,5 kg |
| IP Klasse | IP40 |
| Temperaturbereich | Im Betrieb: -30°C bis + 45°C Lagernd: -10°C bis + 55°C |
| Produkthighlights | Quick-Lock-System, Magnetic Fast-Rigg, Climbable Frame, Fast Replaceable Backbox |
| Zertifizierungen |    EMC |

